



Down Firing..or..Front Firing

ICS, is for In-Cabinet Speaker. Placing conventional speakers in cabinets, or near corners or walls causes the sound to become cupped and chesty. Snell ICS speakers are referenced from our acclaimed "in-room" models, then re-engineered for the boundaries and conditions found in cabinets and millwork. Furthermore, the ICS models are hand-finished in black texture paint, ideal for these invisible locations.

The ICS Sub300, with its innovative mechanical design, can be either front or down firing. The cleverly designed enclosure allows the feet and 300 Watt amplifier to be repositioned so that the long-throw, 10" woofer can be placed firing downward, for a "slot grille" application, or forward firing when in millwork with a full faced grille. Derived from the Basis 300, the ICS Sub300 is a compact 15" cube, capable of first octave bass at levels 110dB, making it the perfect anchor for better home theater systems.

ICS Sub300

| | |
|----------------------|----------------------------------------------------------------|
| Design | Bass Reflex, Powered Subwoofer |
| Frequency Response | 25Hz-150Hz±3dB |
| Amplifier Power | 300 Watts |
| Crossover | Variable 50-150Hz |
| Maximum Output @30Hz | 110dB |
| Placement | Front Firing or Down firing, Frontwall Recommended |
| Drive Unit | Woofer: 10-inch Treated Paper Cone, 15mm Excursion |
| Inputs/Outputs | L/R Low Pass, Low/High Level Inputs, Full Range Input/Output |
| Controls | Front-Mounted Level Control |
| | Variable Low-Pass |
| | Phase Switch, 0 Degrees/ 180 Degrees |
| | On/Off, Auto On-Off Switch with Instant On, and Turn-Off Delay |
| Video Shielding | Optional |
| Dimensions | Height: 16.5-inches, includes feet (1.5-inches) |
| | Width: 15-inches |
| | Depth: 15-inches |
| Finishes Cabinet: | Black Painted MDF |
| | Most wood and paint finished available for an extra cost |
| Grille: | N/A |
| | www.snellacoustics.com 978-538-6262 978-538-6266fax |